

FUZIR



FUZIR-v combines both THERMAL and DAY OPTIC sensors Fused to a single image to offer a fully THERMAL weapon sight or fully DAY vision weapon sight with the same aiming mark or a fully user selectable fusion of both. Can be coupled to EOTech systems.

FUZIR-i



FUZIR-v



Tél : +33 (06 78 01 77 44 - www.pc-equipment.fr)

FUZIR TECHNICAL SPECIFICATIONS

	FUZIR-i	FUZIR-v
Thermal detector 384 x 288 17µm	✓	✓
	Image intensifier XR5A, Gen 3 ou XD-4	Reticles can be modulated by the user
Variable fusion by unique command	✓	✓
Rail picatinny adaptor	✓	✓
Auxiliary Picatinny rail	✓	✓
Video output	✓	✓
Magnification	1x	2x
Dimensions	271,85 x 108,19 x 62,5 mm	208,6 x 108,2 x 62,5 mm
Weight (without batteries)	1527g	1225 g
Battery runtime	Up to 4 hours	
Waterproof	Up to 20 m for 1 hour	
Power	7 lithium AA batteries	
Operation temperature	-20°C to +55°C	
Storage temperature	-40°C to +65°C	

Tél : +33 (06 78 01 77 44 - www.pc-equipment.fr)

