

LTL-6310

High definition camo camera



Key features

- Image Sensor: 12 Mega Pixels Color CMOS
- Max. Pixel Size: 2560x1920
- Lens: FOV=56°; Auto IR-Cut
- IR Flash: 44 LEDs / 20 m
- LCD Screen: 48x38mm; 480(RGB)*234DOT, 16.7M Color
- Operation Keypad: 6 Keys
- Memory SD Card: 8MB to 32GB
- Picture Size: 5MP/12MP/1.3MP = 2560X1920 / 4000X3000 / 1280x960
- Video Size: 640x480 320x240 30fps. 1280x720 20fps
- PIR Sensitivity High / normal / low / off: High / normal / low / off
- PIR Sensing Distance: 20m (below 25°C with sensor level set to normal)
- Prep PIR Sensing angle: Left and right light beams form an angle of 100°; E ach lens covers 10°
- Main PIR Sensing angle: 35°
- Operation Mode: Day / Night
- Trigger Time: 0.6 Second (When using a 2G SD card)
- Trigger Interval: Programmable, 0sec. - 60min

E-mail : contact@pc-equipment.fr

Tél : +33 (0)6 78 01 77 44 - www.pc-equipment.fr



General specifications

- Number of photos per trigger: Programmable, up to 3
- Video Length: Programmable, 1-60 sec
- Camera + Video: First take picture then video
- Playback Zoom: Up to 16x
- Time Stamp: On/Off; Include serial n°, temperature and moon phase
- Timer: Programmable, On/Off
- Password: Programmable, 4 alphanumeric characters
- Device Serial N°: Programmable, 4 alphanumeric characters
- Time Lapse: Programmable, On/Off; 1 second to 24 hours
- SD Card cycle: No
- language setting: Language depending on country setting
- Power Supply: 12xAA
- External DC Power supply: Plug Size: 4.0x1.7. 6-12V (1 to 2A)
- Stand-by Current: 0.4mA
- Stand-by Time: 4-6 Months with 12xAA batteries
- Auto Power Off: Auto power off in 2 minutes if no keypad input
- Power Consumption: 150mA (+350mA when IR LEDs are lit)
- Low Battery Alert: 4.2 to 4.3V
- Interface: TV out / USB / SD Card and SIM Slot / 6V DC external
- Mounting: Strap or tripod
- Waterproof: IP54
- Operation Temperature: -30 ~+70°C
- Operation Humidity: 5% to 95%
- Certificate: FCC & CE & ROHS



E-mail : contact@pc-equipment.fr
Tél : +33 (0)6 78 01 77 44 - www.pc-equipment.fr

